




WIRE ROPE - 6 x 19 CLASS




6 x 25 FILLER WIRE WITH FIBER CORE



6 x 19 SEALE WITH IWRC



6 x 25 FILLER WIRE WITH IWRC



6 x 26 WARRINGTON SEALE WITH IWRC

According to Federal Specification RR-W-4100, preformed, right regular lay, medium lubrication. Read important warnings and information preceding wire rope section.


Diameter in Inches	FIBER CORE (IPS)	
	Approx. Weight per foot in Pounds	Breaking Strength in Tons*
1/4	.105	2.74
5/16	.164	4.26
3/8	.236	6.10
7/16	.32	8.27
1/2	.42	10.7
9/16	.53	13.5
5/8	.66	16.7
3/4	.95	23.8
7/8	1.29	32.2
1	1.68	41.8
1.1/8	2.13	52.6
1.1/4	2.63	64.6
1.3/8	3.18	77.7
1.1/2	3.78	92.0
1.3/4	5.15	124.0
2	6.72	160.0
2.1/4	8.51	200.0
2.1/2	10.5	244.0

Diameter in Inches	IWRC (EIPS)	
	Approx. Weight per foot in Pounds	Breaking Strength in Tons*
1/4	.116	3.4
5/16	.18	5.27
3/8	.26	7.55
7/16	.35	10.2
1/2	.46	13.3
9/16	.59	16.8
5/8	.72	20.6
3/4	1.04	29.4
7/8	1.42	39.8
1	1.85	51.7
1.1/8	2.34	65.0
1.1/4	2.89	79.9
1.3/8	3.50	96.0
1.1/2	4.16	114.0
1.5/8	4.88	132.0
1.3/4	5.67	153.0
2	7.39	198.0
2.1/4	9.36	247.0
2.3/8	10.4	274.0
2.1/2	11.6	302.0


NOTE: Lang lay, left lay, alternate lay, seale available in some sizes.

*Listed for comparison only. Actual operating loads may vary, but should never exceed the recommended design factor or 20% of catalog Breaking Strength.

WIRE ROPE - 6 x 37 CLASS



6 x 36 WARRINGTON
SEALE WITH FIBER CORE



6 x 36 WARRINGTON
SEALE WITH IWRC

According to Federal-Specification RR-W-4100, preformed, right regular lay, medium lubrication.
Read important warnings and information preceding wire rope section.

Diameter in Inches	FIBER CORE (IPS)	
	Approx. Weight per foot in Pounds	Breaking Strength in Tons*
1/4	.105	2.74
5/16	.164	4.26
3/8	.236	6.10
7/16	.32	8.27
1/2	.42	10.7
9/16	.53	13.5
5/8	.66	16.7
3/4	.95	23.8
7/8	1.29	32.2
1	1.68	41.8
1.1/8	2.13	52.6
1.1/4	2.63	64.6
1.3/8	3.18	77.7
1.1/2	3.78	92.0
1.3/4	5.15	124.0
2	6.72	160.0
2.1/4	8.51	200.0
2.1/2	10.5	244.0

Diameter in Inches	IWRC (EIPS)	
	Approx. Weight per foot in Pounds	Breaking Strength in Tons*
1/4	.116	3.4
5/16	.18	5.27
3/8	.26	7.55
7/16	.35	10.2
1/2	.46	13.3
9/16	.59	16.8
5/8	.72	20.6
3/4	1.04	29.4
7/8	1.42	39.8
1	1.85	51.7
1.1/8	2.34	65.0
1.1/4	2.89	79.9
1.3/8	3.50	96.0
1.1/2	4.16	114.0
1.5/8	4.88	132.0
1.3/4	5.67	153.0
2	7.39	198.0
2.1/4	9.36	247.0
2.1/2	11.6	302.0
2.3/4	14.0	368.0
3	16.6	428.0

*Listed for comparison only. Actual operating loads may vary, but should never exceed the recommended design factor or 20% of catalog Breaking Strength.