


These wire ropes are specially designed for use when rotation must be kept to a minimum. Strict adherence to breaking-in procedures and proper handling during use are extremely important with these ropes.

Read important warnings and information preceding wire rope section.

## 19 x 7 ROTATION RESISTANT

According to Federal Specification RR-W-4100. WSC, bright, medium lube, preformed, EIPS.




19 x 7 ROTATION RESISTANT  
WITH WIRE STRAND CORE

Diameter Inches	Approx. Weight per Foot in Pound	Breaking Strength in Tons*
1/4	.113	2.17
5/16	.177	4.30
3/8	.25	6.15
7/16	.35	8.33
1/2	.45	10.8
9/16	.58	13.6
5/8	.71	16.8
3/4	1.02	24.0
7/8	1.39	32.5
1	1.82	42.2
1.1/8	2.30	53.1

## 8 x 25 ROTATION RESISTANT

According to Federal Specification RR-W-4100. IWRC, bright, medium lube, preformed, EIPS.



8 x 25 ROTATION RESISTANT  
WITH IWRC

Diameter Inches	Approx. Weight per Foot in Pound	Breaking Strength in Tons*
3/8	.26	6.63
1/2	.47	11.6
9/16	.60	14.7
5/8	.73	18.1
3/4	1.06	25.9
7/8	1.44	35.0
1	1.88	45.5